

GB

🦀 CompAir

Efficient on-site oil / water_separators

Responsible disposal of compressed air condensate



Unrivalled performance and efficiency

Let CompAir help you be compliant

Environmental regulations strictly prohibit the discharge of oily wastes and chemicals, including the condensate drained from a compressed air system. This mixture of oil and water is classified as hazardous industrial waste, and the discharge of untreated compressor condensate into foul sewers is prohibited.

Compressor condensate must be either collected or treated before disposal using an oil water separator. Oil water separators remove lubricants from compressed air condensate ensuring environmentally friendly disposal. Considering that compressor condensate consists of approximately 95% water, it makes financial sense to separate the oil from the condensate before disposing of waste. Untreated condensate disposal is costly as it is charged by volume.

Every end-user that operates a compressed air system should have a condensate waste management program in place, not only to abide by laws and regulations but also to practice environmental and ecological responsibility. CompAir oil water separators are a reliable, efficient, cost-effective, and environmentally friendly solution for on-site discharge of condensate from air compressors.

Modular design for enhanced performance

Modern industrial working environments present a host of challenges for effective and long-lasting oil water separation including ambient humidity and extreme temperatures, different coolant types, excessive operating hours, equipment age, compressor loading and residual oil.

To meet these challenges, CompAir separators offer different sizes to match the customers needs. They feature adsorption media that withdraws and permanently adsorbs the lubricants.

Features are your benefits

Pre-filter removes contaminants No fouling and clogging

Meets compressor flow requirements

Up to 60 m³/min


Complies with environmental regulations

Minimised fluid disposal costs

Streamlined design Reliable operation with reduced maintenance



How it works



- 1. Oily water flows through the diffuser
- First chamber, multiple Polypropylene media captures oil
- Second chamber, Carbon media further removes oil
- 4. Clean water exits separator



Every compressed air system should have a condensate waste management program in place, not only to abide by laws and regulations but also to practice environmental and ecological responsibility.

The responsible choice

By minimising the cost associated with the disposal of fluids, and keeping them out of the environment, CompAir oil water separators help you to stay compliant with environmental regulations and avoid costly fines. The separator is also designed to operate with minimal maintenance or downtime, resulting in no mess or overflow.

CompAir separators provide condensate discharge levels < 10 ppm at standard conditions.

Guaranteed adsorption of a variety of coolants

Polypropylene and carbon media are effective on a big variety of polyalphaolefins lubricants and mineral oils available in the market.

Multiple sizing options

CompAir oil water separators come in 10 standard sizes, handling air flow from 2.5 to 60 m³/min. The media is designed to last up to 6 months at 8,000 hours/year of operation and up to 12 months at 4,000 hours/year. Each model has standardised, modular media bags.

5



Model	Capacity	Inlet Connection	Outlet Connection	Dimensions [mm]			Weight
	[m³/min]	Inch (BSPP)	Inch (BSPP)	Height	Width	Depth	[kg]
CCS25	2.5	1/2	1/2	588	176	176	6.5
CCS35	3.5	1/2	1/2	588	176	176	7
CCS50	5	1/2	1/2	646	512	172	9.5
CCS100	10	2 x ½	1/2	813	705	260	17.5
CCS150	15	2 x ½	1/2	813	705	260	20
CCS200	20	2 x ½	1/2	813	705	260	22.5
CCS300	30	2 x ½	1/2	1042	952	351	44.5
CCS400	40	2 x ½	1/2	1042	952	351	50
CCS500	50	2 x ¾	3⁄4	1240	1060	416	65
CCS600	60	2 x ¾	3⁄4	1240	1060	416	78

Technical Data

Trust CompAir air treatment equipment

A modern production system and process demands increasing levels of air quality, and compressed air operators need to ensure that the downstream equipment also delivers on it 100%.

The new downstream portfolio manufactured by CompAir utilising the latest technology provides an energy efficient solution at lowest life cycle costs. The same quality, performance, and efficiency standards delivered by the compressors can now be enjoyed from the air treatment range.

Investment in a manufacturing site, in addition to the support teams, ensures that compressed air operators don't need to worry about the quality of their compressed air – quality that is key to ensuring maximum production efficiency and investment protection.

CompAir compressed air product range

Advanced Compressor Technology Lubricated

- Rotary Screw
- > Fixed and Regulated Speed
- Piston
- Portable

Oil-Free

- Water Injected Screw
- > Fixed and Regulated Speed• Two Stage Screw
- Fixed and Regulated Speed
- Piston
- High Speed Centrifugal Quantima®
- Rotary Scroll

Complete Air Treatment Range

- Filter
- Refrigerant and Desiccant Dryer
- Condensate Management
- Heat of Compression Dryer
- Nitrogen Generator

Modern Control Systems

- CompAir DELCOS Controllers
- SmartAir Master Sequencer
- iConn Smart Flow Management

CompAir policy is one of continuous improvement and we therefore reserve the right to alter specifications and prices without prior notice. All products are sold subject to the Company's conditions of sale.

Value Added Services

- Professional Air Audit
- Performance Reporting
- Leak Detection

Leading Customer Support

- Custom Engineered Solutions
- Local Service Centres
- Genuine CompAir Parts
 and Lubricants